

# Georg-August-Universität Göttingen



## Line Planning with Minimal Traveling Time

Anita Schöbel and Susanne Scholl

Preprint Nr. 2005-01

Preprint-Serie des  
Instituts für Numerische und Angewandte Mathematik  
Lotzestr. 16-18  
D - 37083 Göttingen

# Line Planning with Minimal Traveling Time

Anita Schöbel

Susanne Scholl

Institut für Numerische und Angewandte Mathematik

Georg-August Universität Göttingen

July 1, 2005

## Abstract

An important strategic element in the planning process of public transportation is the development of a line concept, i.e. to find a set of paths for operating lines on them. So far, most of the models in the literature aim to minimize the costs or to maximize the number of direct travelers. In this paper we present a new approach minimizing the travel times over all customers including penalties for the transfers needed. This approach maximizes the comfort of the passengers and will make the resulting timetable more reliable. To tackle our problem we present integer programming models and suggest a solution approach using Dantzig-Wolfe decomposition for solving the LP-relaxation. Numerical results of real-world instances are presented.

## 1 Motivation and related literature

In the strategic planning process of a public transportation company one important step is to find a suitable line concept, i.e. to define the routes of the bus or railway lines. Given a public transportation network  $PTN = (S, E)$  with its set of stations  $S$  and its set of direct connections  $E$ , a *line* is defined as a path in this network. The *line concept* is the set of all lines offered by the public transportation company, together with their *frequencies*, where the frequency  $f_l$  of a line  $l$  contains the number of vehicles serving line  $l$  within the planning period considered. The *frequency of an edge*  $e$ , on the other hand, is the number of vehicles running along the edge.

The line planning problem has been well studied in the literature. For an early contribution we refer to Dienst, see [Die78]. The many models given after this time can be roughly classified into the following two types. In a *cost-oriented approach* the goal is to find a line concept serving all customers and minimizing the costs for the public transportation company. The basic cost model has been suggested in Claessens et al., see [ZCvD96], where a binary (linear) programming formulation has been given. A solution approach by branch and cut has been developed in [GvHK04]. In [Bus98] an alternative formulation with integer variables has been proposed. In [BLL04] Bussieck et al. present a fast solution approach combining nonlinear techniques with integer programming.

In [Goo04] and [GvHK02] the authors get rid of the assumption that the passengers are assigned a priori for example by modal split to different types of trains. This is done by assigning a certain *type* to every node in the PTN, representing for example the size of the station. Then the type of a line determines the stations they pass. For example a line of type 1 stops at every station it passes, a line of type 2 will not halt at a station of type 1 but at every station of type 2 or higher. Several models, correctness and equivalence proofs are presented.

Recently, a fast heuristic variable fixing procedure which combines non-linear techniques with integer programming is proposed in [BLL04].

In [Goo04] a model that reconsiders the stations at which the trains stop for a given line plan. This model is used to determine the halting stations in such a way that the total travel time of passengers is minimized. Lagrangian relaxation is used to find lower bounds for this problem. Preprocessing and tree search techniques augment the efficiency of the branch&bound framework.

A new approach is to take into account that the behavior of the customers depends on the design of the lines. A first cost-oriented model including such demand changes was treated with simulated annealing in two diploma theses in cooperation with *Deutsche Bahn*, see [Kli00, Sch01].

A second class of models are the *customer-oriented approaches*. In the *direct travelers approach* by Bussieck et al. [BKZ96] (see also [Bus98]) the goal is to maximize the number of direct travelers (i.e. customers that need not change the line to reach their destination). As constraint, the number of vehicles running along an edge is restricted for each edge in the PTN, i.e. upper and lower bounds on the allowed frequencies on each edge are taken into account.

Although the latter model is a customer-oriented approach it maximizes the amount of one group of customers but without considering the remaining ones which might have very many transfers during their trips. It also does not take into account the travel times for the customers: Sometimes it is preferable to have a transfer but reach the destination earlier instead of sitting in the same line for the whole trip but having a large detour.

A recent work by Quak [Qua03] treats line planning for buses instead of trains. He develops a two phase algorithm with the construction of the lines in the first and setting of frequencies and departure times in the second phase. In contrary to the other models he is not taking lines out of a given line pool but constructs them from the scratch, which is the main part of his work.

[BGP05] considers the pure travel time of the passengers without transfer times and generates the lines dynamically.

In [LMMF04] also the selection of the key station sites is taken into account. These stations are thus connected to lines in an optimization process.

In this work we develop a new model which allows to sum over all travel times over all customers including penalties for the transfers needed. The first ideas for this model have been presented in [SS03]. We also show how different frequencies of the lines can be taken into account. The remainder of the paper is organized as follows. In Section 2 we introduce the new line planning model, discuss its complexity in Section 3 and then describe and discuss five integer programming models in Section 4. We

present two ways to solve the LP-relaxation, one based on Dantzig-Wolfe decomposition (see Section 5). Finally, we present numerical results based on a real-world application of German Rail (DB).

## 2 Basic definitions

A *public transportation network* is a finite, undirected graph  $PTN = (S, E)$  with a node set  $S$  representing stops or stations, and an edge set  $E$ , where each edge  $\{u, v\}$  indicates that there exists a direct ride from station  $u$  to station  $v$  (i.e., a ride that does not pass any other station in between). For each edge  $\{u, v\}$  we assume that the driving time  $t_{uv}$  is known.

We assume the PTN as given and fixed. We further assume that a *line pool*  $\mathcal{L}$  is given, consisting of a set of paths in the PTN. Each line  $l \in \mathcal{L}$  is specified by a sequence of stations, or, equivalently, by a sequence of edges. Let  $E(l)$  be the set of edges belonging to line  $l$ . Given a station  $u \in S$  we furthermore define  $\mathcal{L}(u) = \{l \in \mathcal{L} : u \in l\}$  as the set of all lines passing through  $u$ .

Moreover, let  $\mathcal{R} \subseteq S \times S$  denote the set of all origin-destination pairs  $(s, t)$  where  $w_{st}$  is the number of customers wishing to travel from station  $s$  to station  $t$ .

The line planning problem then is to choose a subset of lines  $L \in \mathcal{L}$ , together with their frequencies, which

- allows each customer to travel from its origin to its destination,
- is not too costly, and
- minimizes the “inconvenience” for the customers.

In the literature, the main customer-oriented approach dealing with the inconvenience of the customers is the approach of [Bus98] (see also [BKZ96]) in which the number of direct travelers is maximized. In our paper, however, we deal with the sum of *all* transfers over all customers. On a first glance, the problem to minimize the number of transfers seems to be similar to maximizing the number of direct travelers. That is in general not the case, as the following example demonstrates.

Note that considering the number of transfers only would lead to solutions with very long lines, serving all origin-destination pairs directly but having large detours for the customers. To avoid this we determine not only a line concept, but also a path for each origin-destination pair and count the number of transfers **and** the length of the paths in the objective function. This is specified next.

Given a set of lines  $L \subseteq \mathcal{L}$ , a customer can travel from its origin  $s$  to its destination  $t$ , if there exists an  $s$ - $t$ -path  $P$  in the PTN only using edges in  $\{E(l) : l \in L\}$ . The “inconvenience” of such a path is then approximated by the weighted sum of the traveling time along the path and the number of transfers, i.e.

$$\text{inconvenience}(P) = k_1 \text{Time}_P + k_2 \text{Transfers}_P.$$

On the other hand, the cost of the line concept  $L \subseteq \mathcal{L}$  is calculated by adding the costs  $C_l$  for each line  $l \in L$ , assuming that such costs  $C_l$  are known beforehand.

The *line planning problem* hence is to find a feasible set of lines  $L \subseteq \mathcal{L}$  together with a path  $P$  for each origin-destination pair, such that the costs of the line concept do not exceed a given budget  $B$  and such that the sum of all inconveniences over all paths is minimized.

Since the capacity of a vehicle is not arbitrarily large, we have to extend the basic problem to include frequencies of the lines. This makes sure that there are enough vehicles along each edge to transport all passengers. If each origin-destination pair can be served, the line concept is called *feasible*. We remark that often, the number of vehicles running along the same edge is also bounded from above, e.g., for safety reasons.

### 3 Complexity Results

In this section we first show that the line planning problem as defined above is NP-hard, even in a very simple case, corresponding to  $k_1 = 0$  in the above definition.

**Theorem 3.1.** *The line planning problem is NP-complete, even if*

- *we only count the number of transfers in the objective function,*
- *the PTN is a linear graph.*
- *all costs  $C_l$  are equal to one.*

*Proof.* In the decision version, the line planning problem in the above case can be written as follows:

Given a graph  $\text{PTN} = (S, E)$  with weights  $c_e$  for each  $e \in E$ , origin-destination pairs  $\mathcal{R}$ , and a budget  $B$ , does there exist a feasible set of  $B$  lines with less than  $K$  transfers?

We reduce the set covering problem to the line planning problem: Given a set covering problem in its integer programming formulation

$$\min\{1_n x : Ax \geq 1_m, x \in \{0, 1\}^n\}$$

with an 0-1  $m \times n$  matrix  $A$ , and  $1_k \in \mathbb{R}^k$  the vector with a 1 in each component, we construct a line planning problem as follows:

We define the PTN as a linear graph with  $2m$  nodes  $S = \{s_1, t_1, s_2, t_2, \dots, s_m, t_m\}$  and edges  $E = \{(s_1, t_1), (t_1, s_2), (s_2, t_2), (t_2, s_3), \dots, (s_m, t_m)\}$ . We define an origin-destination pair for each row of  $A$ ,

$$\mathcal{R} = \{(s_i, t_i) : i = 1, \dots, m\}.$$

For column  $j$  of  $A$  we construct a line  $l_j$  passing through nodes  $s_i$  and  $t_i$  if  $a_{ij} = 1$ .

As an example, Figure 1 shows the line planning problem obtained from a set covering problem with

$$A = \begin{pmatrix} 1 & 1 & 0 & 0 \\ 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 \\ 1 & 0 & 1 & 0 \end{pmatrix}$$

Setting  $K = 0$  we hence have to show that a cover with less than  $B$  elements exists if and only if the line planning problem has a solution




Figure 1: Construction of the line planning problem in the proof of Theorem 3.1.

in which all passengers can travel without changing lines. Due to our construction this is true and hence the theorem holds. ■

A question that might arise in this context, is what happens if the lines need not be chosen from a given line pool, but can be constructed as any path. Some of the basic cost models become very easy in this case, but unfortunately, the complexity status of the line planning problem treated in this paper does not change which can be shown by reduction to the Hamiltonian path problem (see [Sch05]).

## 4 A model for the line planning problem

To model the line planning problem as integer program we use the PTN to construct a directed graph, the so-called *change&go network*  $G_{CG} = (\mathcal{V}, \mathcal{E})$  as follows:

We extend the set  $S$  of stations to a set  $\mathcal{V}$  of nodes with nodes representing either station-line-pairs (change&go nodes:  $\mathcal{V}_{CG}$ ) or the origins and destinations of the customers (origin-destination nodes:  $\mathcal{V}_{OD}$ ), i.e.  $\mathcal{V} := \mathcal{V}_{CG} \cup \mathcal{V}_{OD}$  with

- $\mathcal{V}_{CG} := \{(s, l) \in S \times \mathcal{L} : l \in \mathcal{L}(s)\}$  (set of all station-line-pairs)
- $\mathcal{V}_{OD} := \{(s, 0) : (s, t) \in \mathcal{R} \text{ or } (t, s) \in \mathcal{R}\}$  (origin-destination nodes)

The new set of edges  $\mathcal{E}$  consists of directed edges between nodes of the same stations (representing that customers board or unboard a vehicle or change lines) and edges between nodes of the same line (representing the driving activities):

$$\mathcal{E} := \mathcal{E}_{change} \cup \mathcal{E}_{OD} \cup \mathcal{E}_{go}$$

with

- $\mathcal{E}_{change} := \{((s, l_1), (s, l_2)) \in \mathcal{V}_{CG} \times \mathcal{V}_{CG}\}$  (changing edges)
- $\mathcal{E}_l := \{((s, l), (s', l)) \in \mathcal{V}_{CG} \times \mathcal{V}_{CG} : (s, s') \in E\}$  (driving edges of line  $l \in \mathcal{L}$ )
- $\mathcal{E}_{go} := \bigcup_{l \in \mathcal{L}} \mathcal{E}_l$  (driving edges)
- $\mathcal{E}_{OD} := \{((s, 0), (s, l)) \in \mathcal{V}_{OD} \times \mathcal{V}_{CG} \text{ and } ((t, l), (t, 0)) \in \mathcal{V}_{CG} \times \mathcal{V}_{OD} : (s, t) \in \mathcal{R}\}$  (origin-destination edges)

We define weights on all edges  $e \in \mathcal{E}$  of the change&go network representing the inconvenience customers have when using edge  $e$ . Given a set of lines  $L \subseteq \mathcal{L}$  we then can determine the lines the customers are likely to use by calculating a shortest path in the change&go network for each single origin-destination pair. Therefore the choice of the edge costs  $c_e$  is very important. We give two examples:

1. Customers only count transfers:

$$c_e = \begin{cases} 1 & : e \in \mathcal{E}_{change} \\ 0 & : \text{else} \end{cases}$$

Note that in this case, it is possible to shrink the change&go network to a network with  $|\mathcal{L}| + |S|$  nodes and  $|\mathcal{E}_{change}| + |\mathcal{E}_{OD}|$  edges.

2. Real travel time:

$$c_e = \begin{cases} 0 & : e \in \mathcal{E}_{OD} \\ \text{travel time in minutes} & : e \in \mathcal{E}_{go} \\ \text{time needed for changing platform} & : e \in \mathcal{E}_{change} \end{cases}$$

More specific, to model the line planning problem as defined in Section 2, we set

$$c_e = \begin{cases} 0 & \text{if } e \in \mathcal{E}_{OD} \\ k_1 t_{uv} & \text{if } e = ((u, l), (v, l)) \in \mathcal{E}_{go} \\ k_2 & \text{if } e \in \mathcal{E}_{change} \end{cases}$$

Since we assume that customers behave selfish we need an implicit calculation of shortest paths (with respect to the weights  $c_e$ ) within our model. This is obtained by solving the following network flow problem for each origin-destination pair  $(s, t) \in \mathcal{R}$ .

$$\theta x_{st} = b_{st},$$

where

- $\theta \in \mathbb{Z}^{|\mathcal{V}| \times |\mathcal{E}|}$  is the node-arc-incidence matrix of  $G_{CG}$ ,
- $b_{st} \in \mathbb{Z}^{|\mathcal{V}|}$  is defined by

$$b_{st}^i = \begin{cases} 1 & : i = (s, 0) \\ -1 & : i = (t, 0) \\ 0 & : \text{else} \end{cases}$$

- and  $x_{st}^e \in \{0, 1\}$  are the variables, where  $x_{st}^e = 1$  if and only if edge  $e$  is used on a shortest dipath from node  $(s, 0)$  to  $(t, 0)$  in  $G_{CG}$ .

To specify the lines in the line concept we introduce variables  $y_l \in \{0, 1\}$  for each line  $l \in \mathcal{L}$ , which are set to 1 if and only if line  $l$  is chosen to be in the line concept. Our model, *Line Planning with Minimal Travel Times* (LPMT) can now be presented.

(LPMT1)

$$\min \sum_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}} w_{st} c_e x_{st}^e \quad (1)$$

$$s.t. \quad \sum_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}^l} x_{st}^e \leq |\mathcal{R}| |\mathcal{E}^l| y_l \quad \forall l \in \mathcal{L} \quad (2)$$

$$\theta x_{st} = b_{st} \quad \forall (s, t) \in \mathcal{R} \quad (3)$$

$$\sum_{l \in \mathcal{L}} C_l y_l \leq B \quad (4)$$

$$x_{st}^e, y_l \in \{0, 1\} \quad \forall (s, t) \in \mathcal{R}, e \in \mathcal{E}, l \in \mathcal{L} \quad (5)$$

Constraint (2) makes sure that a line must be included in the line concept if the line is used by some origin-destination pair. Constraint (3) models the selfish behavior of the customers, i.e., that customers use shortest paths according to the weights  $c_e$ .

Having only constraints (2) and (3), the best line concept from a customer-oriented point of view would be to introduce all lines of the line pool. This is certainly no option for a public transportation company, since running a line is costly. Let  $C_l$  be an estimation of the costs for running line  $l$  and let  $B$  be the budget the public transportation company is willing to spend. Then the budget constraint (4) takes the economic aspects into account.

The objective function we use is customer-oriented: We sum up the costs  $\sum_{e \in \mathcal{E}} w_{st} c_e x_{st}^e$  of a shortest path from  $s$  to  $t$  for each origin-destination pair  $(s, t) \in \mathcal{R}$ , i.e., we minimize the average costs of the customers.

We get three more formulations of this problem by substituting constraints (2) by one of the following constraints

$$\sum_{(s,t) \in \mathcal{R}} x_{st}^e \leq |\mathcal{R}| y_l \quad \forall l \in \mathcal{L}, e \in \mathcal{E}^l \quad (6)$$

$$\sum_{e \in \mathcal{E}^l} x_{st}^e \leq |\mathcal{E}^l| y_l \quad \forall l \in \mathcal{L}, (s, t) \in \mathcal{R} \quad (7)$$

$$x_{st}^e \leq y_l \quad \forall (s, t) \in \mathcal{R}, e \in \mathcal{E}^l : l \in \mathcal{L} \quad (8)$$

We denote the formulation using constraints (6) (LPMT2), using (7) (LPMT3), and using (8) (LPMT4).

In [Sch05] we have shown that these formulations are equivalent, i.e. they are valid IP formulations from the same integer set. Nevertheless the bounds provided by the corresponding LP-relaxations differ.

**Definition 4.1.** ([Wol98]) A polyhedron  $P \subseteq \mathbb{R}^n$  is a formulation for a set  $X \subseteq \mathbb{Z}^n$  if and only if  $X = P \cap (\mathbb{Z}^n)$ .

Given a set  $X \subseteq \mathbb{R}^n$ , and two formulations  $P_A$  and  $P_B$  for  $X$ ,  $P_A$  is a stronger formulation than  $P_B$  if  $P_A \subset P_B$ .

Given two formulations  $P_A$  and  $P_B$  for the same integer set  $X$  with  $P_A$  stronger than  $P_B$ , then

$$\min_{x \in X} cx \geq \min_{x \in P_A} cx \geq \min_{x \in P_B} cx.$$

**Theorem 4.2.** The convex hull of the integer set described by formulation (LPMT1) is denoted by  $P_1$ . The corresponding polyhedra described by formulation (LPMT2), (LPMT3), and (LPMT4) are denoted by  $P_2$ ,  $P_3$ , and  $P_4$ , respectively. Then, the following holds:

- $P_4$  is stronger than  $P_1$ ,  $P_2$ , and  $P_3$ .
- $P_3$  is stronger than  $P_1$ .
- $P_2$  is stronger than  $P_1$ .
- Comparing  $P_3$  and  $P_2$ , none of them is stronger than the other.

The proof can be found in [Sch05]. Note that in real world instances (LPMT3) comes out to be in most cases stronger than (LPMT2), see Section 5.1.



In (LPMT) we implicitly assume that all customers traveling from station  $s$  to station  $t$  choose the same path in the change&go network, i.e., the same set of lines. This can be done if edge capacities are neglected in (LPMT). In practice, this is usually not the case, since each vehicle only can transport a limited number of customers and usually there is only a limited number of vehicles possible along each line (e.g. due to safety rules). In the following, we therefore present an extension of (LPMT) taking into account the number of vehicles on each line in a given time period. Consequently, this formulation allows to split customers along different paths from  $s$  to  $t$  in the change&go network  $G_{CG}$ .

Let  $N$  denote the capacity of a vehicle and let the new variables  $f_l \in \mathbb{N}$  contain the frequency of line  $l$ , i.e., the number of vehicles running along line  $l$  within a given time period. Furthermore we choose variables  $x_{st}^e \in \mathbb{N}$  and change the vector  $b_{st}$  to

$$b_{st}^i = \begin{cases} w_{st} & \text{if } i = (s, 0) \\ -w_{st} & \text{if } i = (t, 0) \\ 0 & \text{else} \end{cases}$$

Then the *Line Planning Model with minimal transfers and frequencies* (LPMTF) is the following:

(LPMTF)

$$\min \sum_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}} c_e x_{st}^e \quad (9)$$

$$s.t. \quad \frac{1}{N} \sum_{(s,t) \in \mathcal{R}} x_{st}^e \leq f_l \quad \forall l \in \mathcal{L}, e \in \mathcal{E}_l \quad (10)$$

$$\theta x_{st} = b_{st} \quad \forall (s, t) \in \mathcal{R} \quad (11)$$

$$\sum_{l \in \mathcal{L}} C_l f_l \leq B \quad (12)$$

$$\sum_{l \in \mathcal{L}: k \in \mathcal{E}_l} f_l \leq f_k^{max} \quad \forall k \in E \quad (13)$$

$$x_{st}^e, f_l \in \mathbb{N} \quad \forall (s, t) \in \mathcal{R}, e \in \mathcal{E}, l \in \mathcal{L} \quad (14)$$

Constraints (10) make sure that the frequency of a line is high enough to transport the passengers. If  $f_l = 0$ , the line  $l$  is not chosen in the line concept. Constraints (11) are flow conservation constraints routing the passengers on the shortest possible paths. Note that the  $x_{st}^e$  variables can take integer values, such that passengers may choose different paths for the same origin-destination pair. Constraint (12) is again the budget constraint but with costs for each vehicle of a line (which are multiplied by the frequency to get the costs of the line). The capacity constraint (13) may be included if upper bounds for the frequencies are present.

## 5 Solving the LP-relaxation

As we have shown in Section 3 the line planning problem is NP-hard, and, moreover in real-world instances, gets huge. But fortunately the formulations of (LPMT) and (LPMTF) have block diagonal structure with only few coupling constraints. Moreover, in both models, all blocks are totally unimodular since they represent network flow problems.

In Section 5.1 we identify cases in which the solution of the LP-relaxation can be found by solving shortest path problems. If this does not work we have to take advantage of the block diagonal structure by using a Dantzig-Wolfe decomposition, which is shown in Section 5.2.

## 5.1 Using the trivial solution

**Definition 5.1.** A trivial solution  $(\bar{x}, \bar{y}^1), (\bar{x}, \bar{y}^2), (\bar{x}, \bar{y}^3), (\bar{x}, \bar{y}^4)$  of (LPMT1), (LPMT2), (LPMT3), (LPMT4), respectively, is defined as the solution  $\bar{x}_{st}^e$  of the shortest path problems

$$\theta x_{st} = b_{st} \quad \forall (s, t) \in \mathcal{R}$$

on the change $\mathcal{E}$ go-network constructed of all lines of the line pool and

$$\begin{aligned} \bar{y}_l^1 &:= \frac{\sum_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}^l} \bar{x}_{st}^e}{|\mathcal{E}^l| |\mathcal{R}|} & \forall l \in \mathcal{L} & \text{ (for (LPMT1))} \\ \bar{y}_l^2 &:= \frac{\max_{e \in \mathcal{E}^l} \sum_{(s,t) \in \mathcal{R}} \bar{x}_{st}^e}{|\mathcal{R}|} & \forall l \in \mathcal{L} & \text{ (for (LPMT2))} \\ \bar{y}_l^3 &:= \frac{\max_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}^l} \bar{x}_{st}^e}{|\mathcal{E}^l|} & \forall l \in \mathcal{L} & \text{ (for (LPMT3))} \\ \bar{y}_l^4 &:= \max_{(s,t) \in \mathcal{R}} \max_{e \in \mathcal{E}^l} \bar{x}_{st}^e & \forall l \in \mathcal{L} & \text{ (for (LPMT4))} \end{aligned}$$

It is in general not unique and need not to be feasible in the sense that it fulfills the budget constraint.

In real world instances it appears quite often that a trivial solution is an optimal solution of the LP-relaxation of (LPMT1). This is clear since the right hand sides  $|\mathcal{R}| |\mathcal{E}^l|$  of the coupling constraints (2) are chosen such that all passengers could use all edges of all lines. In real world only few edges of the network are used and so  $K_l := \sum_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}^l} x_{st}^e$  is much smaller than  $|\mathcal{R}| |\mathcal{E}^l|$ , hence

$$\sum_{l \in \mathcal{L}} C_l \bar{y}_l^1 = \sum_{l \in \mathcal{L}} C_l \frac{K_l}{|\mathcal{E}^l| |\mathcal{R}|} \leq B$$

is often satisfied.

The following Lemma generalizes this for the other formulations. The proof can be found in [Sch05].

**Lemma 5.2.** Let  $i \in \{1, 2, 3, 4\}$  and let  $(\bar{x}, \bar{y}^i)$  be a trivial solution of (LPMTi), as defined in Definition 5.1. If

$$Ti := \sum_{l \in \mathcal{L}} C_l \bar{y}_l^i \leq B$$

is satisfied, the trivial solution  $(\bar{x}, \bar{y}^i)$  is an optimal solution of the (LPMTi). Note that for  $i = 4$  the solution  $(\bar{x}, \bar{y}^4)$  of the LP-relaxation of (LPMT4) is integer and thus if  $T4 \leq B$  holds, the trivial solution is an optimal solution to the original problem.

In Table 1 we see the  $Ti$ -values for different line pool sizes, where the line costs are set to one. Note that in this case a value below one means that the trivial solution is always the optimal solution independently of

No.	$ \mathcal{L} $	obj.val.	T1	T2	T3	T4
1	10	2271.3	0.69	0.99	9.53	10
2	50	9459.9	0.20	0.35	25.31	48
3	100	24780.0	0.13	0.29	41.83	96
4	132	31654.2	0.11	0.26	53.12	129
5	200	15128.9	0.07	0.19	54.89	197
6	250	19096.0	0.05	0.16	61.07	235
7	275	20118.2	0.04	0.15	63.47	252
8	300	26598.3	0.06	0.19	72.35	282
9	330	26817.7	0.04	0.16	74.44	302
10	350	26450.0	0.07	0.23	90.04	331
11	375	27517.8	0.06	0.20	90.75	345
12	400	34781.3	0.06	0.20	100.05	370
13	423	35135.5	0.06	0.20	102.19	389

Table 1: Minimal budgets such that trivial solution is an optimal solution of the LP-relaxation of the different formulations of the (LPMT), see Lemma 5.2.

the choice of the budget. Only if the given budget is smaller than the  $Ti$  value, the trivial solution is not a feasible solution of the LP-relaxation of (LPMTi). Thus, table 1 demonstrates the difference of the strength of the formulations. The higher the  $Ti$ -value, the better the lower bound provided by the corresponding formulation.

We see that in real world instances the bound provided by (LPMT3) is much stronger than (LPMT2) even if we could not show this in general. This is due to the fact that there exists an instance in which (LPMT2) is stronger than (LPMT3) but in real world this hardly ever happens.

Regarding the  $T4$ -values, we recall that in this formulation the  $\bar{y}_l^4$  are integer valued and since all  $C_l = 1$  this means that if we are allowed to choose more than  $T4$  lines out of the line pool, every passenger can travel on shortest path. If our budget is smaller, some passengers have a detour. In this case we have to use other methods to solve the problem like the Dantzig-Wolfe approach explained in the next section.

## 5.2 Using Dantzig-Wolfe decomposition

In this section we present an approach for solving the LP-relaxation of the (LPMT) formulations using Dantzig-Wolfe decomposition. The method can also be applied for solving (LPMTF) since the model structure is very similar. However, the numerical results deal with (LPMT). We will present two different decompositions. Since the blocks in both decompositions are totally unimodular, we know that the bound provided by the Master formulations is as good as the bound of the LP-relaxation (see [Sch05]).

### 5.2.1 One block for each origin-destination pair

(LPMT1(LP))

$$\min \sum_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}} c_{st}^e x_{st}^e \quad (15)$$

$$\begin{aligned} \sum_{(s,t) \in \mathcal{R}} \sum_{e \in \mathcal{E}} x_{st}^e &\leq |\mathcal{R}| |\mathcal{E}^l| y_l \quad \forall l \in \mathcal{L} \\ \sum_{l \in \mathcal{L}} C_l y_l &\leq B \end{aligned}$$

coupling constraints

$X^{s_1, t_1}$

$X^{s_2, t_2}$

$\ddots$

$X^{s_r, t_r}$

}

$|\mathcal{R}|$  blocks

where  $X^{st} := \{x_{st} \in \mathbb{R}^{|\mathcal{E}|} : \theta x_{st} = b_{st}, 0 \leq x_{st}^e \leq 1, \forall e \in \mathcal{E}\}$   
The coupling constraints can be written as

$$\begin{aligned} -A_Y y + \sum_{(s,t) \in \mathcal{R}} A_X x_{st} &\leq 0 \\ C y &\leq B \end{aligned}$$

where

- $A_X$  is an  $|\mathcal{L}| \times |\mathcal{E}|$  matrix given by elements  $a_{le} = 1$ , if  $e \in \mathcal{E}_l$ , zero otherwise. It is equal for each origin-destination pair.
- $A_Y$  is an  $|\mathcal{L}| \times |\mathcal{L}|$  diagonal matrix containing  $|\mathcal{R}| |\mathcal{E}^l|$  as its  $l$ th diagonal element.
- $C$  is the line cost vector  $(C_1, \dots, C_{|\mathcal{L}|})$ .

So, we get the following coefficient matrix of (LPMT1):

$$\begin{pmatrix} -A_Y & A_X & \dots & A_X \\ C & & & \\ & \theta & & \\ & & \ddots & \\ & & & \theta \end{pmatrix}$$

Defining the *weight-cost-parameters*  $c_{st}^e := w_{st} c_e$ , we get the following Master Problem corresponding to decomposition (15):

(Master 1)

$$\begin{aligned} z = \min \quad & \sum_{(s,t) \in \mathcal{R}} \sum_i (c_{st} x_{st}^{(i)}) \alpha_{st}^i \\ \text{s.t.} \quad & \sum_{(s,t) \in \mathcal{R}} \sum_i (A_X x_{st}^{(i)}) \alpha_{st}^i - A_Y y + I v = 0 \\ & \sum_{l \in \mathcal{L}} C_l y_l \leq B \\ & \sum_i \alpha_{st}^i = 1 \quad \forall (s,t) \in \mathcal{R} \\ & y_l \geq 1 \quad \forall l \in \mathcal{L} \\ & v_l, \alpha_{st}^i, y_l \geq 0 \end{aligned}$$

where the  $|\mathcal{L}|$ -vector  $v$  are slack variables, and  $x_{st}^{(i)}$  are the extreme points of  $X^{st}$ . This problem has  $|\mathcal{L}| + 1$  coupling constraints and  $|\mathcal{R}|$  convexity constraints.

For each  $(s, t) \in \mathcal{R}$  we obtain the following subproblem:

$$z_{st} = \min_{s.t. \quad x_{st} \in X^{st}} (c_{st} - \pi A_X) x_{st} - \mu_{st}$$

where  $\{\pi_i\}_{i \in \mathcal{L}}$  are the dual variables of the coupling constraints, and  $\{\mu_{st}\}_{(s,t) \in \mathcal{R}}$  are the dual variables of the convexity constraints.

The  $X^{st}$  blocks correspond to shortest path problems which are known to be totally unimodular, hence the  $x_{st}^{(i)}$ -values are in  $\{0, 1\}^{|\mathcal{E}|}$ . The formulations (LPMT2), (LPMT3), (LPMT4) as well as (LPMTF) can be reformulated analogously.

### 5.2.2 One block for all origin-destination pairs

If we treat the  $X^{st}$ -blocks as one block we get the following reformulation:

(LPMT1(LP))

$$\min \sum_{e \in \mathcal{E}} c^e x^e \tag{16}$$

$$\boxed{\begin{array}{l} \sum_{e \in \mathcal{E}} x^e \leq |\mathcal{R}| |\mathcal{E}^l| y_l \quad \forall l \in \mathcal{L} \\ \sum_{l \in \mathcal{L}} C_l y_l \leq B \end{array}} \quad \text{coupling constraints}$$

$$\boxed{X} \quad \text{1 block}$$

with  $X := \{x \in \mathbb{R}^{|\mathcal{E}|} : x^e = \sum_{(s,t) \in \mathcal{R}} x_{st}^e \quad \forall e \in \mathcal{E}, x_{st} \in X^{st}\}$  and  $c^e := \sum_{(s,t) \in \mathcal{R}} c_{st}^e$ .

The Master Program corresponding to decomposition (16) is

(Master 2)

$$\begin{aligned} z = \min \quad & \sum_i (c x^{(i)}) \alpha^i \\ s.t. \quad & \sum_i (A_X x^{(i)}) \alpha^i - A_Y y + I v = 0 \\ & \sum_{l \in \mathcal{L}} C(l) y_l \leq B \\ & \sum_i \alpha^i = 1 \\ & v_l, \alpha^i, y_l \geq 0 \end{aligned}$$

where the  $|\mathcal{L}|$ -vector  $v$  are slack variables, and  $x^{(i)}$  are the extreme points of  $X$ . This problem has  $|\mathcal{L}| + 1$  coupling constraints and one convexity constraints.

The subproblem of the  $X$ -block is

$$\begin{aligned} z = \min \quad & \sum_{(s,t) \in \mathcal{R}} (c_{st} - \pi A_X) x_{st} - \mu \\ s.t. \quad & x_{st} \in X^{st} \end{aligned}$$

where  $x^e := \sum_{(s,t) \in \mathcal{R}} x_{st}^e$  and  $\{\pi_i\}_{i \in \mathcal{L}}$  are the dual variables of the coupling constraints,  $\mu$  is the dual variable of the convexity constraint.

As in the previous formulation, the  $x^{(i)}$ -values are integer because they are the component wise sum over shortest path problem solution which are in  $\{0, 1\}$ . In this decomposition we loose the information of the exact paths of the customers which are needed in (LPMT3), (LPMT4) and (LPMTF) and thus this Master cannot be adapted to these formulations.

No.	$ \mathcal{L} $	$ \mathcal{R} $	CPU1	CPU2
0	3	2	0.05	0.1
1	10	2602	1	228
2	50	4766	3	606
3	100	11219	16	8706
4	132	18238	48	M
5	200	10126	78	M
6	250	13246	329	M
7	275	14071	691	M
8	300	17507	1171	M
9	330	18433	1911	M
10	350	17095	1814	M
11	375	18350	2727	M
12	400	22191	4789	M
13	423	22756	8715	M

Table 2: CPU times of the LP-relaxation of (LPMT1) and (LPMT3) using Dantzig-Wolfe approach with (Master2) and (Master1), respectively, for different line pool sizes. M denotes "out of memory".

### 5.2.3 Implementation

We implemented the Dantzig-Wolfe decomposition approach of (LPMT) using Xpress MP 2003 and Microsoft Visual C++ 6.0. The CPU times of this section are based on a 3.06 GHz Intel4 processor with 512 MB RAM. The subproblems were solved with Dijkstra's shortest path algorithm.

In column 'CPU1' of table 2 we see the CPU times in seconds for solving the LP-relaxation of (LPMT1) using Dantzig-Wolfe approach with (Master2) for different line pool sizes of the network of German long distance trains. In column 'CPU2' we see the CPU times in seconds for solving the LP-relaxation of (LPMT3) using Dantzig-Wolfe approach with (Master1). We have mentioned that the lower bound provided by (LPMT3) is stronger than (LPMT1) and so the computation times increase in this case. We see, that using our approach it is possible to solve the LP-relaxation of (LPMT3) for medium sized networks within reasonable time. Note that the size of the problem not only depends on the size of the line pool but on the number of origin-destination pairs and the size of the PTN which may be much smaller e.g. in urban underground networks. Solving the LP-relaxation of the weaker (LPMT1) formulation is possible even for big real world instances like the long distance network of German railway within two and a half hours.

As we have seen, the main problem of our approach is the size of the change&go-network depending mainly on the size of the line pool. A wise choice of a possibly small line pool is therefore advisable. On the other hand it makes sense to analyze the underlying PTN. For example if two lines go parallel for a long time, it is sufficient to add changing edges only at the first and the last station. Also arcs between stations without changing possibility can be shrunk to decrease the size of the network.

## 6 Conclusions

We developed integer programming models for the line planning problem with the goal to minimize the travel times over all customers including penalties for the transfers needed and proposed an extension that includes frequencies. We showed that the problem is NP-hard. Since the problem gets huge, a straightforward solution of the LP relaxation is not possible. We showed that in many real world cases the trivial solution is optimal or, if it is infeasible, it can be found by a solution approach based on Dantzig-Wolfe decomposition. Computational results for various real world instances and different decompositions were presented.

We are currently working on a branch&price algorithm and heuristics to get an integer solution.

## References

- [BGP05] R. Borndörfer, M. Grötschel, and M.E. Pfetsch. A path-based model for line planning in public transport. ZIP-Report 05-18, Konrad-Zuse-Zentrum für Informationstechnik Berlin, 2005.
- [BKZ96] M.R. Bussieck, P. Kreuzer, and U.T. Zimmermann. Optimal lines for railway systems. *European Journal of Operational Research*, 96(1):54–63, 1996.
- [BLL04] M.R. Bussieck, T. Lindner, and M.E. Lübbecke. A fast algorithm for near cost optimal line plans. *mathematical methods of operational research*, 59(2):205–220, 2004.
- [Bus98] M.R. Bussieck. *Optimal lines in public transport*. PhD thesis, Technische Universität Braunschweig, 1998.
- [Die78] H. Dienst. *Linienplanung im spurgeführten Personenverkehr mit Hilfe eines heuristischen Verfahrens*. PhD thesis, Technische Universität Braunschweig, 1978.
- [Goo04] J.-W. Goossens. *Models and algorithms for railway line planning problems*. PhD thesis, University of Maastricht, 2004.
- [GvHK02] J.-W. Goossens, C.P.M. van Hoesel, and L.G. Kroon. On solving multi-type line planning problems. Technical Report RM/02/009, University of Maastricht, 2002. METEOR Research Memorandum.
- [GvHK04] J.-W. Goossens, S. van Hoesel, and L.G. Kroon. A branch-and-cut approach for solving railway line-planning problems. *Transportation Science*, 38(3):379–393, 2004.
- [Kli00] H. Klingele. Verfahren zur Optimierung eines Linienkonzeptes der Deutschen Bahn AG. Master’s thesis, Universität Karlsruhe, 2000.
- [LMMF04] G. Laporte, A. Marín, J.A. Mesa, and Ortega F.A. An integrated methodology for rapid transit network design. In *Proceedings of ATMOS 2004, 4th Workshop on Algorithmic Methods and Models for Optimization of Railways, Bergen, Norway, September 16 - 17, 2004*, 2004.
- [Qua03] C.B. Quak. Bus line planning, Master’s thesis, TU Delft, 2003.

- [Sch01] M. Schmidt. Modelle zur Linienoptimierung im Zugverkehr unter Berücksichtigung der Nachfrage. Master's thesis, Universität Kaiserslautern, 2001.
- [Sch05] S. Scholl. *Customer-oriented line planning*. PhD thesis, Technische Universität Kaiserslautern, 2005.
- [SS03] A. Schöbel and S. Scholl. Planung von Linien mit minimalen Umsteigevorgängen. In D. Mattfeld, editor, *Proceedings of the GOR-workshop on "Optimierung im öffentlichen Nahverkehr"*, pages 69–89, 2003. <http://server3.winforms.phil.tu-bs.de/gor/tagung34/>.
- [Wol98] L.A. Wolsey. *Integer Programming*. John Wiley & Sons, 1998.
- [ZCvD96] M.T. Zwaneveld, M.T. Claessens, and N.M. van Dijk. A new method to determine the cost optimal allocation of passenger lines. In *Defence or Attack: Proceedings 2nd TRAIL Phd Congress 1996, part 2*. TRAIL Research School, 1996.



Institut für Numerische und Angewandte Mathematik  
Universität Göttingen  
Lotzestr. 16-18  
D - 37083 Göttingen

Telefon: 0551/394512  
Telefax: 0551/393944

Email: [trapp@math.uni-goettingen.de](mailto:trapp@math.uni-goettingen.de) URL: <http://www.num.math.uni-goettingen.de>

### **Verzeichnis der erschienenen Preprints:**

1. A. Schöbel, S. Scholl: Line Planning with Minimal Traveling Time